




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

| | | | |
|---|-----------|---|------------------------------|
| (51) International Patent Classification ⁵ : | | (11) International Publication Number: | WO 95/24658 |
| G01V 1/16, 1/28, 3/12, G01H 1/00, 11/10, H04B 13/02, H01Q 1/46, H04R 9/00 | A1 | (43) International Publication Date: | 14 September 1995 (14.09.95) |
| (21) International Application Number: PCT/US94/02626 | | (81) Designated States: AT, AU, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, ES, FI, GB, GE, HU, JP, KP, KR, KZ, LK, LU, LV, MG, MN, MW, NL, NO, NZ, PL, PT, RO, RU, SD, SE, SI, SK, TT, UA, US, UZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). | |
| (22) International Filing Date: 10 March 1994 (10.03.94) | | | |
| (71)(72) Applicants and Inventors: FARNSWORTH, David, F. [US/US]; 1934 S.W. Stringtown Road, Forest Grove, OR 97116 (US). PARK, Larry, A. [US/US]; 50631 N.W. Gheen Road, Manning, OR 97125 (US). | | | |
| (74) Agents: BIRDWELL, William, A. et al.; Suite 1260, 900 S.W. 5th Avenue, Portland, OR 97204 (US). | | Published With international search report. | |

(54) Title: METHOD AND APPARATUS FOR DETECTING LOCAL PRECURSOR SEISMIC ACTIVITY

(57) Abstract

A method and apparatus for sensing one or more physical parameters, including acoustic waves having frequencies from approximately 0 Hz to 15 Hz, electromagnetic waves having frequencies from approximately 0 Hz through 35 Hz and seismic waves having frequencies from approximately 0 Hz through 15 Hz, and detecting precursor seismic activity indicated therein. Acoustic waves are sensed using an infrasonic transducer (22) that produces an electrical signal representative of such waves. Electromagnetic waves are sensed using a suitable antenna (13), the antenna preferably comprising AC power lines. The antenna produces an electrical signal representative of such waves. Seismic waves are sensed using an accelerometer (28) that produces an electrical signal representative of such waves. In one embodiment of the invention, the electrical signals are routed to a signal conditioning mechanism (16) that converts the signals into detect signals suitable for detection of precursor seismic activity, the detect signals being, in turn, routed to a processing unit (32) for detection of precursor seismic activity.



BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

| | | | | | |
|----|--------------------------|----|---------------------------------------|----|--------------------------|
| AT | Austria | GB | United Kingdom | MR | Mauritania |
| AU | Australia | GE | Georgia | MW | Malawi |
| BB | Barbados | GN | Guinea | NE | Niger |
| BE | Belgium | GR | Greece | NL | Netherlands |
| BF | Burkina Faso | HU | Hungary | NO | Norway |
| BG | Bulgaria | IE | Ireland | NZ | New Zealand |
| BJ | Benin | IT | Italy | PL | Poland |
| BR | Brazil | JP | Japan | PT | Portugal |
| BY | Belarus | KE | Kenya | RO | Romania |
| CA | Canada | KG | Kyrgyzstan | RU | Russian Federation |
| CF | Central African Republic | KP | Democratic People's Republic of Korea | SD | Sudan |
| CG | Congo | KR | Republic of Korea | SE | Sweden |
| CH | Switzerland | KZ | Kazakhstan | SI | Slovenia |
| CI | Côte d'Ivoire | LJ | Liechtenstein | SK | Slovakia |
| CM | Cameroon | LK | Sri Lanka | SN | Senegal |
| CN | China | LU | Luxembourg | TD | Chad |
| CS | Czechoslovakia | LV | Latvia | TG | Togo |
| CZ | Czech Republic | MC | Monaco | TJ | Tajikistan |
| DE | Germany | MD | Republic of Moldova | TT | Trinidad and Tobago |
| DK | Denmark | MG | Madagascar | UA | Ukraine |
| ES | Spain | ML | Mali | US | United States of America |
| FI | Finland | MN | Mongolia | UZ | Uzbekistan |
| FR | France | | | VN | Viet Nam |
| GA | Gabon | | | | |

BEST AVAILABLE COPY

METHOD AND APPARATUS FOR DETECTING LOCAL PRECURSOR SEISMIC ACTIVITY

This application relates to a method and apparatus for detecting seismic activity, particularly for detecting local precursor seismic activity so as to forecast an impending earthquake.

The often devastating toll taken by earthquakes in life and property is well known. It has long been recognized that the toll could be reduced if people within an impending quake's focal area were warned to prepare. Although preparation is unlikely to prevent structural damage to commercial and residential buildings, or to infrastructure such as bridges and roadways, preparation could reduce deaths and serious injuries, for instance by people seeking appropriate shelter or retreating from dangerous locations, such as from unreinforced brick buildings. Moreover, preparation is likely to reduce the psychological trauma often attributable to an earthquake's sudden onslaught. In addition, preparation is likely to reduce personal property casualty such as that related to structural or utility failures, and the fires often associated therewith. Accordingly, it is desirable to provide a mechanism for forecasting the possible occurrence of an earthquake.

An earthquake's toll results from the seismic waves defining the earthquake. Seismic waves include two types: body waves and surface waves. Body waves comprise primary (or P) waves and secondary (or S) waves that propagate within the earth's body. P waves are longitudinal waves that alternately push (compress) and pull (dilate) the ground in the direction of propagation. S waves are transverse waves that shear the ground in planes perpendicular to the direction of propagation.

Surface waves comprise Love waves and Rayleigh waves that propagate at or near the earth's surface. Love waves shear the ground sideways at right angles to the direction of propagation, much like S waves, but without S waves' vertical shearing. Rayleigh waves displace the earth both vertically and horizontally in a vertical plane that lies in the

direction of propagation, whereby a particle of earth will travel an elliptical path as the wave passes, much like a water molecule in rolling ocean waves.

Body waves travel more rapidly than surface waves. Of the surface waves, Love waves generally travel faster than Rayleigh waves and, of the body waves, P waves generally travel faster than S waves. When an earthquake is occurring, the P waves are felt first, like a thud or blow, and thereafter the S waves arrive, as indicated by up-and-down and side-to-side motion. Thereafter, the surface waves strike, causing the ground to shake side-to-side and to roll.

The body and surface waves generally are monitored during an earthquake to gauge the earthquake's intensity. Being contemporaneous with and defining earthquakes, these waves cannot be used for forecasting. Forecasting relies on identification of other physical parameters that, in their occurrence or variance, indicate an impending earthquake. These parameters, when indicating an impending earthquake, are sometimes referred to herein as "precursor seismic activity".

Techniques have heretofore been proposed for forecasting earthquakes relying on sensing various physical parameters. These parameters have included changes in animal behavior patterns, build-up of strain in the rocks of the earth's crust, changes in seismic P wave velocities, uplift and tilt of the earth, increases in the emission of radon gas, and changes in the earth's electrical resistivity, magnetic and electromagnetic fields, or current. Other physical parameters, as well as apparatuses and techniques for sensing these parameters, have also been proposed in attempts to detect precursor seismic activity so as to forecast impending earthquakes. However, the techniques using these parameters have not provided adequate forecasting due to, among other things, difficulty in detection of precursor seismic activity therefrom.

Accordingly, there is a need for an improved method and apparatus for detecting seismic activity, particularly

precursor seismic activity so as to forecast an impending earthquake.

Summary of the Invention

The present invention fulfills the aforementioned need by providing a method and apparatus that senses one or more of several physical parameters, including infrasonic atmospheric acoustic waves, electromagnetic waves having frequencies from approximately 0 Hz through 35 Hz and seismic waves having frequencies from approximately 0 Hz through 15 Hz, so as to detect precursor seismic activity. The acoustic waves are sensed using an infrasonic transducer that produces an electrical signal representative of sensed acoustic waves. The electromagnetic waves are sensed using a suitable antenna. The antenna preferably comprises the power grid so as to accommodate the long wavelength of these extremely low frequency waves. The antenna produces an electrical signal representative of sensed electromagnetic waves. The seismic waves are sensed by using an accelerometer sensitive to the low frequency, long wavelength, low amplitude and associated acceleration of these waves, and produces an electrical signal representative of sensed seismic waves.

The electrical signals, so produced, are used to detect precursor seismic activity. In one embodiment of the invention, all of the electrical signals are routed to an analog-to-digital converter that converts the signals into digital signals which, in turn, are routed to a processing unit for detection of precursor seismic activity. The detection mechanism preferably is implemented in digital signal processing (DSP) circuitry.

In another embodiment, the electrical signal representative of the electromagnetic radiation is passed through a low-pass filter to defeat undesirable high-frequency components, and is then passed through one or more high-Q band-pass filters to isolate one or more desired frequency components. The isolated components are then converted to digital signals that are provided to the processing unit for detection of precursor seismic activity. The signals

representative of the acoustic waves and seismic waves in this embodiment preferably are processed, and precursor seismic activity detected, substantially similarly to that of the first embodiment.

5 The processing unit preferably controls an I/O stage. The I/O stage alerts the user of a potentially impending earthquake in any of various ways, e.g., using audio, display or other alarms. The processing unit triggers the I/O stage's alarms when precursor seismic activity is detected.

10 Accordingly, it is a principle object of the present invention to provide a novel and improved method and apparatus for detecting seismic activity.

15 It is another object of the present invention to provide such a method and apparatus wherein seismic activity is detected so as to forecast an impending earthquake.

 It is a further object of the present invention to provide such a method and apparatus so as to forecast an impending earthquake by sensing a physical parameter so as to detect precursor seismic activity indicated therein.

20 It is yet another object of the present invention to provide such a method and apparatus wherein more than one precursor physical parameter is sensed to detect precursor seismic activity, so as to forecast an impending earthquake.

25 It is yet a further object of the present invention to provide such a method and apparatus wherein more than one physical parameter is sensed so that forecasts of an impending earthquake are made at selected times in advance of the quake, each advance time associated with detections using one of the sensed physical parameters.

30 It is another object of the present invention to provide such a method and apparatus wherein infrasonic atmospheric acoustic waves, electromagnetic waves in the 1-35 Hz frequency band, and seismic waves having frequencies in the 1-15 Hz frequency band are sensed, alone or in combination.

35 It is a further object of the present invention to provide such a method and apparatus using digital signal processing circuits to recognize waveforms indicative of an impending earthquake.

It is yet another object of the present invention to provide such a method and apparatus for forecasting an impending earthquake with sufficient advance notice to permit preparatory measures to be taken, so as to reduce deaths, injuries, psychological trauma and property damage that may result from the earthquake.

It is yet a further object of the present invention to provide such method and apparatus that is easy to use, economical, reliable and portable.

The foregoing and other objects, features and advantages of the invention will be more readily understood upon consideration of the following detailed description of the invention, taken in conjunction with the accompanying drawings.

Brief Description of the Drawings

Figure 1 is a block diagram of an apparatus for sensing predetermined electromagnetic, acoustic and seismic waves and detecting precursor seismic activity therefrom, according to the present invention.

Figure 2 is perspective view of a mechanism for sensing acoustic waves according to the present invention.

Figure 3 is a side, partial cross section of the mechanism of Figure 2, taken along line 3-3 thereof.

Figure 4 is a block diagram of a mechanism for detecting precursor seismic activity using sensed acoustic waves or seismic waves, according to the present invention.

Figure 5 is a block diagram of a mechanism for detecting precursor seismic activity using sensed electromagnetic waves, according to the present invention.

Figure 6 is a block diagram of an alternative mechanism for detecting precursor seismic activity from sensed electromagnetic radiation, according to the present invention.

Figures 7A and 7B are schematic diagrams of the circuit of Figure 6, according to the present invention.

Figure 8 is schematic diagram of a frequency detection channel (FDC) shown in Figures 7A and 7B, according to the present invention.

Figure 9 is a flowchart of a process for detecting precursor seismic activity using the mechanism of Figure 6, according to the present invention.

Detailed Description of the Invention

5 Referring to Figure 1, an apparatus for detecting precursor seismic activity includes an acoustic wave sensing mechanism 10, an electromagnetic wave sensing mechanism 12, a seismic wave sensing mechanism 14, a signal conditioning mechanism 16, a detection mechanism 18 and an input/output (I/O) stage 20.

10 The physical parameters sensed by respective sensing mechanisms 10, 12 and 14 include (i) atmospheric acoustic waves (ii) electromagnetic waves, and (iii) seismic waves. These waves individually, or in combination, are associated with precursor seismic activity. Accordingly, proper sensing and detection of these waves individually, or in combination, provides for forecasting of earthquakes. The acoustic waves correspond to seismic waves associated with precursor seismic activity, the seismic waves propagating in the earth and ultimately emerging at the surface of the earth for transmission into the atmosphere as infrasonic acoustic waves inaudible to humans. Forecasts based on sensing these acoustic waves typically precede an associated quake by approximately 3 days. Precursor seismic activity is also detectable in electromagnetic waves having frequencies from approximately 0 Hz through 35 Hz, or seismic waves having frequencies from approximately 0 Hz through 15 Hz, or both. Forecasts based on sensing these electromagnetic waves, which are characterized by low amplitude and long wavelengths, typically precede an associated earthquake by approximately a week or more. Similarly, forecasts based on sensing these seismic waves, which also are characterized by low amplitudes and long wavelengths, typically precede an associated earthquake by time periods measured in seconds up to minutes.

35 The acoustic wave sensing mechanism 10 preferably comprises a transducer 22 sensitive to predetermined acoustic waves propagating in the atmosphere. The transducer 22, in a

preferred embodiment, senses acoustic waves having frequencies from approximately 0 Hz through 15 Hz, i.e., infrasonic acoustic waves. In addition, the transducer 22 preferably is tuned so as to substantially reject acoustic waves outside that bandwidth. It is to be recognized, however, that transducers sensitive to other, broader or narrower, bandwidths may be used without departing from the principles of the invention.

The transducer 22 produces an electrical signal representative of sensed acoustic waves. Preferably, the transducer 22 is not sensitive to ambient atmospheric pressure, or temperature, or changes in either. However, where the transducer is sensitive to pressure or temperature, or changes therein, measures preferably are implemented to defeat any such sensitivity. To that end, the transducer 22 as shown in Figure 1 is enclosed in a sealed chamber 24 so as to defeat sensitivity to pressure or changes therein. In addition, temperature sensor 26 is employed which senses ambient temperature and produces a signal representative thereof so as to provide for compensation of any temperature sensitivity of the transducer 22. Compensation preferably is implemented by characterizing and responding to the transducer's deviations from ideal performance relative to temperature. It is to be recognized that various techniques for excluding, compensating or otherwise defeating any transducer sensitivity to atmospheric pressure or temperature, or changes therein (or other ambient phenomena, or spurious waves associated therewith, to which the transducer 22 may be sensitive) are known in the art and may be employed without departing from the principles of the invention.

In using the apparatus, the transducer 22 preferably is installed for substantially optimal reception of infrasonic acoustic waves, so as to maximize the range and reliability of the apparatus. The infrasonic acoustic waves not only are generally inaudible to people, but also are of such low amplitude that they can only be sensed using a sensing mechanism 10, such as the transducer 22. However, sensing using a transducer 22 may be impeded, particularly by damping.

Damping occurs, for instance, as the waves propagate away from the earth's surface. Accordingly, the transducer 22 preferably is installed on or adjacent the earth's surface. Preferably, the transducer 22 is installed within 25 feet of the earth's surface.

A preferred embodiment of the transducer 22, as shown in Figures 2 and 3, comprises a body 200, diaphragm 202, a first transmission element 204, a connector 206, bearing elements 208, a coil 210, and a magnet 212. As further described below, the diaphragm 202 is attached to one end of the body 200. In turn, the first transmission element 204, at one end, is affixed to the diaphragm 202 and at the other end, is affixed to one end of the connector 206. The connector 206 is affixed at its other end to the coil 210.

The body 200 has a chamber 214 disposed in one end thereof, the chamber 214 comprising an outer portion 216, middle portion 218 and an inner portion 220. The body 200 preferably is constructed using ceramic materials, but it is to be recognized that other materials, such as plastics or metals, may be employed without departing from the principles of the invention. The body 200 preferably has a substantially cylindrical shape, having a length of about 1.5 inches and a cross-sectional diameter of about 1 inch.

The diaphragm 202 preferably has a substantially domed shape, the dome having an enclosed volume 222 and a base diameter substantially equal to the cross-sectional diameter of the body 200. At its base, the diaphragm 202 is affixed to the body 200, adjacent the outer portion 216 of the body's chamber 214. The diaphragm 202, so affixed, seals the body 200, thereby creating a cavity 224. The cavity 224 comprises the chamber 214 and the diaphragm's enclosed volume 222, and has a predetermined atmospheric pressure therein. The predetermined atmospheric pressure preferably provides for substantially mid-range operation of the transducer 22. That is, the pressure is not so low or high (relative to the range of ambient atmospheric pressures likely to be encountered in operation) that the transducer's sensitivity to infrasonic acoustic waves is substantially impeded. In the alternative,

the cavity 224 may be vented to the ambient atmosphere by means of a small hole in the body 200 so that static pressures on both sides of the diaphragm 202 are substantially equalized and only sound pressure is sensed. The diaphragm 202

5 preferably is constructed using ceramic materials, and has a thickness of 0.001 to 0.002 inches, and is affixed to the body 200 using an adhesive capable of creating and maintaining the seal. It is to be recognized, however, that other shapes, materials, thicknesses, or affixation agents or mechanisms, such as ultrasonic welding, may be employed without departing from the principles of the invention.

10 The first transmission element 204 preferably is constructed using ceramic materials, and is affixed to the diaphragm 202 using ultrasonic welding. The transmission element 204 preferably is fixed at a plurality of points, along a circular line, or over a relatively large surface. It is to be recognized, however, that other materials, affixation agents or mechanisms, or affixation geometries may be employed therefor, without departing from the principles of the invention.

20 The connector 206 preferably comprises a metal pin, although other materials may be used without departing from the principles of the invention.

25 The coil preferably comprises 60 gauge wire, wound around a second transmission element 224, and having output leads 228. The second transmission element 224 preferably is constructed using ceramic materials and has a longitudinal aperture 226 disposed on the end of the element 224 opposite affixation to the connector 206. The aperture 226 preferably is shaped as a right-cylinder, as described further below. The coil 210 preferably has a impedance of 168 ohms. It is to be recognized, however, that other materials and shapes may be employed without departing from the principles of the invention.

30 The first transmission element 204, affixed to the diaphragm 202, is disposed in the outer portion 216 of the chamber 214, extending up into the diaphragm's enclosed volume 222. In turn, the connector 206 is disposed through the

chamber's middle portion 218, and the coil 210 is disposed in the chamber's inner chamber 220. The connector 206 preferably is aligned and slidably supported in the middle portion 218 by the bearing elements 208. The bearing elements 208 preferably
5 comprise three ruby jewels disposed at the approximate midpoint of the chamber's middle portion 218, substantially at 120° to one another.

The first transmission element 204, the connector 206 and the coil 210 are disposed so as to be aligned in respective
10 portions 216, 218 and 220. In addition, the first transmission element 204, the connector 206 and the coil 208 preferably have cross-sectional shapes substantially corresponding to the shapes of the respective portions 216, 218 and 220, all having smaller cross-sectional dimensions
15 than those respective portions. For example, the outer and inner portions 216 and 220 of the chamber 214, as shown, have substantially round cross-sectional shapes and the first transmission element 204 and the coil 210 disposed
20 respectively therein preferably have substantially round cross-sectional shapes of smaller diameters than the portions 216 and 220. In addition, the coil 210 has a length L_1 that is shorter by a predetermined amount than the length L_2 of the chamber's inner portion 220. The difference between L_1 and L_2 preferably is determined so as to accommodate the range of
25 displacement that coil 210 is likely to encounter in operation.

Having such dispositions, shapes and dimensions relative to respective portions 216, 218 and 220, the first
30 transmission element 204, the connector 206 and the coil 210 move substantially unimpeded within the respective portions 216, 218 and 220. It is to be recognized, however, that the cross-sectional shapes of the first transmission element 204, the connector 206 and the coil 210 may correspond to shapes
35 other than the shapes of respective portions 216, 218 and 220 without departing from the principles of the invention, provided the relative shapes allow substantially unimpeded movement therebetween.

The magnet 212 is affixed to the body 200 at the closed end of the chamber's inner portion 220. Although the magnet 212 preferably is a permanent magnet, it is to be recognized that the magnet 212 may be constructed using any suitable material without departing from the principles of the invention. It is also to be recognized that the magnet 212 may be affixed to the body 200 using adhesive or other affixation agents or mechanisms without departing from the principles of the invention. The magnet 212 is shaped so that the magnet is accommodated within the aperture 226 of the coil's second transmission element 224. Because the aperture 226 preferably has a right-cylindrical cross-sectional shape, the magnet 212 preferably is shaped as a right-cylinder, having a diameter less than that of the aperture 226. The length of the magnet 212 is selected in light of the relative lengths L_1 of the coil 210 and L_2 of the chamber's inner portion 220, respectively, so as to accommodate the range of displacement the coil 210 is likely to encounter in operation.

In operation, the transducer 22 produces an electrical signal representative of sensed acoustic waves, by sensing changes in sound pressure. That is, the infrasonic acoustic waves reciprocally deflect the diaphragm 202. The diaphragm's reciprocal movement is transmitted to the coil 210 by the first transmission element 204 and the connector 206. The coil's movement relative to the magnet 212 generates the electrical signal, according to fundamental principles of physics. The signal is produced at the leads 228. In this embodiment, the transducer 22 is largely insensitive to ambient atmospheric pressure, or changes therein, that relate to weather patterns. Accordingly, the transducer 22 of Figure 2 may be used in the absence of the chamber 24 shown in Figure 1, without departing from the principles of the invention.

The seismic wave sensing mechanism 14 preferably comprises an accelerometer 28 sensitive to predetermined accelerations. The accelerometer 28, in a preferred embodiment, detects accelerations manifest at the earth's surface associated with seismic waves. More specifically, the accelerometer 28 preferably is sensitive to seismic waves

having (i) frequencies from approximately 0 Hz through 15 Hz, and (ii) accelerations on the order of milli-g's, where "g" is the standard unit of acceleration equal to 32.17 ft/sec². In addition, the accelerometer 28 preferably is tuned so as to substantially reject waves having frequencies outside the 0-15 Hz band. It is to be recognized, however, that accelerometers 28 sensitive to other, broader or narrower bandwidths, amplitude ranges or acceleration ranges, may be used without departing from the principles of the invention.

The accelerometer 28 produces an electrical signal representative of sensed seismic waves. Preferably the accelerometer 28 comprises one or more piezoelectric seismic accelerometers, but it is to be recognized that other types of accelerometers, including micromercury switches, may be used without departing from the principles of the invention. Various types of piezoelectric accelerometers are described in the Vibration and Shock Sensor Selection Guide, SSG-601, by PCB Piezotronics, particularly pages 42-43 for low cost accelerometers, and pages 92-105 for general descriptions of operation, configuration, selection and installation. That Guide is hereby incorporated by reference.

The electromagnetic wave sensing mechanism 12 senses predetermined electromagnetic frequencies and produces an electrical signal representative thereof. The sensing mechanism 12, in a preferred embodiment, comprises an antenna sensitive to electromagnetic waves having frequencies from approximately 0 Hz through 35 Hz. It is to be recognized, however, that an antenna sensitive to other, broader or narrower, bandwidths may be used without departing from the principles of the invention.

The electromagnetic wave sensing mechanism 12 preferably employs the AC power lines 13 that are widely used to distribute power from and among power generating facilities and ultimately to end-user's such as homes, office and the like. The AC power lines 13 make up a complex network of wire, often referred to as the power grid, and have characteristics particularly suitable for sensing the predetermined frequencies of electromagnetic waves. First, by

basic principles of antenna design theory, a wire antenna sensitive to electromagnetic waves of approximately 35 Hz preferably has a length on the order of 10^6 kilometers, which length increases for lower frequencies. The AC power lines 13 provide a practical wire antenna having a suitably long overall length. Second, the low-frequency electromagnetic waves associated with precursor seismic activity tend to propagate substantially vertically from the earth's surface and are of relatively low power, such that an antenna sensing such waves preferably is disposed horizontal to and adjacent the earth's surface. The AC power lines 13 provide such antenna as the lines generally are strung substantially horizontally to and relatively close to the earth's surface. Third, the apparatus is intended for use in forecasting earthquakes at geographically diverse locations, so as to require antennas at such locations. The AC power lines 13 substantially blanket vast geographic areas and generally may be individually and readily tapped at homes, offices and other locations where the apparatus is likely to be used. Moreover, in blanketing vast geographic areas, the AC power lines 13 provide an antenna capable of sensing precursor seismic activity that, although relatively remote from the user, may manifest as an earthquake at the user's location. It is to be recognized, however, that the AC power lines 13 inadequately cover some geographic areas and, indeed, leave entirely uncovered other geographic areas; in those areas, the apparatus may be implemented using an electromagnetic wave sensing mechanism 12 comprising an antenna of other design, such as loop or coil antennas, tuned for the predetermined frequency bandwidth.

The respective electrical signals produced by the respective sensing mechanisms 10, 12 and 14 are routed to the signal conditioning mechanism 16. The signal conditioning mechanism 16 conditions the electrical signals so as to produce signals suitable for use by the detection mechanism 18 in the detection of precursor seismic activity. The signal conditioning mechanism 16 may comprise transformers, rectifiers, voltage dividers, filters, amplifiers or

compensation circuitry, in various combinations, so as to, among other things, optimize selectivity and sensitivity, to compensate for non-ideal behavior in the sensing mechanisms 10, 12 or 14, to minimize effects of noise, or to perform other functions. The signal conditioning mechanism 16 preferably produces digital signals, but it is to be recognized that the mechanism 16 could produce analog signals or digital signals, or a combination of both, without departing from the principles of the invention. If digital signals are produced, in particular if the detection mechanism 18 is implemented using digital circuitry, the signal conditioning mechanism 16 preferably comprises, as shown in Figure 1, an analog-to-digital converter (ADC) 30 which converts the respective signals of sensing mechanisms 10, 12 and 14 into digital signals representative of such analog signals and, correspondingly, representative of the sensed acoustic waves, electromagnetic waves, and seismic waves, respectively. (Hereafter, the electrical signals produced by respective sensing mechanisms 10, 12 and 14 will sometimes be referred to as detect signals.)

The ADC 30 preferably also receives the temperature signal produced by the temperature sensor 26. The ADC 30 converts that signal to a digital temperature signal for use by the detection mechanism 18 in compensating for any temperature-related inaccuracies of the acoustic wave sensing mechanism 10.

The signal conditioning mechanism 16, as respects the electromagnetic wave sensing mechanism 12, preferably comprises a standard three-prong plug 58 insertable in a standard three-receptacle wall socket 57, as are present in a home, office or the like. The plug 58, when inserted in the socket 57, connects to the sensing mechanism 12, i.e., the AC power lines 13. Preferably the three-prong plug 58 comprises a transformer 59 so as to reduce the line voltage to a voltage level suitable for other signal conditioning operations. The detect signal produced by the transformer 59 is provided to a full wave rectifier 60 having a device ground tap 60A. The device ground tap 60A is coupled to one terminal of a

capacitor 62, and to one input of an amplifier 63. The capacitor's other terminal is coupled to the amplifier's other input and to earth ground, preferably through prong 58A when the plug 58 is inserted in socket 59. So referenced to earth ground, the detect signal is amplified and provided to the ADC 30 for digital conversion. Although as shown the rectifier 60 is employed, it is to be recognized that the rectifier may be omitted from the signal conditioning mechanism 16 without departing from the principles of the invention, as the rectifier's primary purpose is to provide rectified power to power supply circuitry 61. The capacitor 62 preferably is nonpolarized and typically has capacitance of 1-50 microfarads.

As discussed further hereinafter with reference to Figures 6 through 9, additional analog circuitry is employed in a second embodiment of the signal conditioning mechanism respecting signals produced by electromagnetic wave sensing mechanism 12.

The signal conditioning mechanism 16, as respects the acoustic and seismic wave sensing mechanisms 10 and 14, preferably comprises amplifiers 63 for amplifying the respectively-produced detect signals. The amplifiers 63 preferably comprise low noise precision operational amplifiers, for instance MAX414 operational amplifiers manufactured by MAXIM Integrated Products, Inc. of Sunnyvale, California.

The detect signals produced by the signal conditioning mechanism 16 are routed to the detection mechanism 18. The detection mechanism 18 processes the detect signals so as to detect predetermined waveforms generally indicative of precursor seismic activity that may be present in any of the detect signals.

The detection mechanism 18, as shown in Figure 1, comprises a processing unit 32 that receives the detect signals from the ADC 30. The processing unit 32 may be implemented using a programmed microprocessor, programmed digital signal processor, or other processing circuits performing digital signal processing operations. In addition,

the detection mechanisms may be integrated in a single application specific integrated circuit (ASIC), together with some or all of the signal conditioning mechanism 16, or other circuitry, or both. It is to be recognized that the detection mechanism 18 may be implemented in analog circuitry without departing from the principles of the invention.

Turning to Figure 4, the processing unit 32 is shown in functional blocks representative of digital signal processing operations performed on detect signals associated with the acoustic and seismic wave sensing mechanisms 10 and 14. The processing unit 32 is substantially the same for both types of waves, except that the processing unit 32 also performs temperature compensation with respect to the detect signals associated with acoustic waves, as described above, using digital information corresponding to the temperature sensor's signal. It is to be recognized, however, that temperature compensation may be performed outside the detection mechanism 18 without departing from the principles of the invention. It is also to be recognized that various techniques may be employed to exclude, compensate or otherwise detect temperature or other undesirable sensitivities that may be manifest by components other than the acoustic wave sensing mechanism 10, without departing from the principles of the invention. In particular, it is preferred for extreme applications, wherein the apparatus is subject to relatively high temperatures, to provide temperature compensation for all affected circuitry.

The processing operations corresponding to acoustic and seismic waves comprise filter 34, rectifier 36, slope up detector 38, slope down detector 40, slope trigger 42, slope comparator 44, peak detector 46 and seismic magnitude processor 48. In operation, the filter 34 receives detect signals from the signal conditioning mechanism 16. The filter 34 defeats undesirable frequency components present in the detect signals. The undesirable frequency components, as described above, generally are those above 15 Hz. Thence, the filter 34 preferably comprises a low-pass filter having a cut-off frequency substantially of 15 Hz. It is to be recognized,

however, that the filter 34 may be other than a low-pass filter having a 15 Hz cut-off frequency, without departing from the principles of the invention. For example, the filter 34 may have a narrower or wider bandwidth, so as to filter out noise or to pass fundamentals of signal frequency components determined to have forecasting significance and, in so configuring the filter's response, the filter 34 may have characteristics of a band-pass filter or a notch filter, or both.

The detect signal, so filtered, is routed to the rectifier 36. The rectifier 36 preferably is a full-wave rectifier so as to retain substantially all of the remaining detect signal for subsequent processing operations performed by the detection mechanism 18. However, it is to be recognized that a half-wave rectifier may be used without departing from the principles of the invention.

The detect signal, so rectified, is routed to each of the slope up detector 38, the slope down detector 40, the slope trigger 42 and the peak detector 46. The peak detector 46 detects the maximum amplitude of the peaks of the detect signal and provides that information to the seismic magnitude processor 48. The peak detector 46 preferably resets at a predetermined interval, typically every 1 second, so as to provide relatively current information to the processor 48.

The slope up detector 38, slope down detector 40 and slope trigger 42, in conjunction with the slope comparator 44, detect waveforms present in the detect signal indicative of precursor seismic activity. The slope trigger 42 determines when the detect signal crosses a predetermined voltage threshold and the signal's direction at each such crossing, that is whether the signal is increasing or decreasing in amplitude. When such crossing occurs, the slope trigger 42 produces a triggering signal that is routed to the slope up or slope down detector 38 or 40 corresponding to the signal's direction. The triggering signals cause the detectors 38 and 40 to detect the respective slopes of consecutive pairs of upwardly and downwardly directed transitions of the detect signal. The detectors 38 and 40 produce respective upward and

downward slope signals that are routed to and stored by the slope comparator 44. The slope comparator 44 compares the relative magnitudes of the respective slope signals. If the slope comparator 44 determines that the magnitude of the slope of an upwardly directed transition is greater than that of the corresponding downwardly directed transition, the slope comparator 44 produces a predetermined comparator signal that is routed to the seismic magnitude processor 48 to indicate that precursor seismic activity is present. Otherwise, the comparator signal indicates the absence of such activity. So as to compare the slope of an upwardly directed transition with the slope of the associated downwardly directed transition, the slope comparator 44 resets the stored downward slope value upon receipt of each upward slope signal.

The seismic magnitude processor 48, responsive to signals from the slope comparator 44, produces control signals that are routed to the I/O stage 20. For comparator signals associated with seismic waves, the seismic magnitude processor 48 preferably produces a digital signal indicative of the presence or absence of precursor seismic activity. For comparator signals associated with acoustic waves, the seismic magnitude processor 42 preferably produces a digital signal indicative of the presence or absence of precursor seismic activity. If such activity is present, the seismic magnitude processor 48 produces a signal indicative of the potential magnitude of the earthquake likely associated with the detected precursor seismic activity. The seismic magnitude processor 48 determines that magnitude using the current maximum amplitude of the detect signal's peaks, as detected by the peak detector 46. Preferably, the processor 48 is calibrated so as to optimize accuracy in this determination. Calibration may be accomplished by any method known in the art, including by empirically deriving the relationship between amplitude and earthquake magnitude and storing that relationship preferably in the processor 48, either by look-up table, by formula or by other means.

The seismic magnitude processor 48, when calculating the magnitude of a potential earthquake, preferably also adjusts

the calculation to compensate for any temperature-related inaccuracies, as well as for any inaccuracies associated with other ambient phenomena, as described above.

Turning to Figure 5, the detection mechanism 18 is shown in functional blocks representative of digital signal processing operations performed on detect signals associated with the electromagnetic wave sensing mechanism 12. The processing operations comprise filter 50, rectifier 52, presence detector 54, integrator 56 and seismic magnitude processor 55. In operation, the filter 50 and rectifier 52 operate in substantially the same way as described above for, respectively, the filter 34 and the rectifier 36 used in conditioning detect signals associated with the acoustic and seismic wave sensors 10 and 14. However, the filter 50 preferably comprises a low-pass filter having a cut-off frequency substantially of 35 Hz. Moreover, the rectifier 52 preferably comprises a half-wave rectifier.

The EM presence detect 54 receives the rectified detect signal from the rectifier 52, as well as a predetermined threshold signal 53. The EM presence detect 54 compares the amplitude of the detect signal to the threshold signal. If the detect signal amplitude is at or above the threshold signal's amplitude, the EM presence detect 54 produces a presence signal that is routed to the integrator 56. The threshold signal 53 preferably is selected based on various factors, including the desired geographic range of the device (generally higher thresholds correspond to decreased range), and gains and losses of the signal conditioning mechanism 16. The presence signal preferably is a digital signal wherein a first value indicates the presence of precursor seismic activity and a second value indicates the absence of such activity.

The integrator 56 integrates the presence signal over time. The integrator 56 stores and outputs an integrated presence signal that is routed to the processor 55. A non-zero value of the integrated presence signal indicates precursor seismic activity and, thence, indicates that an earthquake is likely to occur. The magnitude of the

integrated presence signal generally is related to the magnitude of the indicated earthquake. That is, the duration of time over which the detect signal remains at or above the threshold signal generally is related directly to the magnitude of the indicated earthquake.

The integrator 56 resets the integrated presence signal if the presence signal indicates the absence of precursor seismic activity for a predetermined period of time. Typically, that period of time is from about 6 to about 20 hours.

The processor 55 receives the integrated presence signal output by the integrator 56 and, responsive thereto, produces signals that are routed to the I/O stage 20. The processor 55 preferably produces a digital signal indicative of the presence or absence of precursor seismic activity and, if such activity is present, the processor 55 preferably produces a signal indicative of the potential magnitude of the earthquake associated with the detected precursor seismic activity. The processor 55 determines that magnitude using the magnitude of the integrated threshold signal. Preferably, the processor 55 is calibrated so as to maximize accuracy in this determination. Calibration may be accomplished by any method known in the art, including by empirically deriving the relationship between the magnitudes, and storing that relationship in the processor 55, either by look-up table, by formula or by other means.

The I/O stage 20 alerts the user of a potentially impending earthquake. As shown in Figure 1, the I/O stage preferably comprises both a display alarm 64 and an audio alarm 66. It is to be recognized, however, that the I/O stage 20 may comprise these or other alarms, individually or in combination, without departing from the principles of the invention.

In operation, the I/O stage 20 receives control signals produced by the seismic magnitude processor 48 and the processor 55 indicative of precursor seismic activity detected in sensed acoustic, electromagnetic and seismic waves. The I/O stage 20, upon receipt of any one or more signals

indicative a potentially impending earthquake, triggers the display alarm 64 or the audio alarm 66, or both. The display alarm 64 preferably comprises an alphanumeric display of the impending earthquake in terms of its magnitude, e.g., a
5 Richter scale display. The display alarm 64 preferably further comprises indicator lights 68 for alerting the user as to whether the alarm is based on detections related to electromagnetic, acoustic or seismic waves. To that end, three indicator lights 68 are employed, each one corresponding
10 to one of the sensing mechanisms 10, 12 and 14. When acoustic and electromagnetic waves concurrently indicate precursor seismic activity, the display alarm 64 reciprocates the displayed information between the two waves, and the indicator lights 68 indicate the detected wave being displayed at any
15 time.

As previously described, precursor seismic activity can be detected at different times in advance of the earthquake. Accordingly, the alarms preferably alert of any likely near-term earthquake. In particular, the audio alarm 66 is
20 responsive to precursor seismic activity detected in seismic waves, because the advance time between such detection and the onslaught of the earthquake is typically on the order of seconds to minutes. Preferably, the audio alarm 66 includes a clear alert corresponding specifically to that detection. For
25 example, the alarm 66 may have a predetermined pitch, cadence or volume, or a combination thereof.

The I/O stage 20 preferably comprises a decoder mechanism 70 for receiving the various signals from the processing unit 32, for decoding those signals and for producing driver
30 signals corresponding to the display alarm 64 and the audio alarm 66. Although the decoder mechanism 70 is shown as a separate element of the I/O stage 20, it is to be recognized that the decoder mechanism 70 may be otherwise implemented without departing from the principles of the invention. For
35 example, the display alarm 64 and the audio alarm 66 may include circuitry for receiving and decoding the signals produced by the processor unit 32 so as to drive the respective alarms. In addition, it is to be recognized that

the decoder mechanism 70 may be integrated in the detection mechanism 18, particularly in the processing unit 32, without departing from the principles of the invention.

Turning to Figures 6 through 9, a second embodiment of the signal conditioning mechanism 16 is shown respecting conditioning the detect signal associated with the electromagnetic wave sensing mechanism 12. As shown in Figure 6, the second embodiment of the signal conditioning mechanism 16 receives the detect signal produced by the electromagnetic wave sensing mechanism 12, routing the detect signal in parallel both to a comparison function 72 and to a filter function 74. The filter function 74 produces frequency components from the detect signal in predetermined bandwidths for interpretation by the detection mechanism 18. The comparison function 72 produces a rejection signal representative of the detect signal, that rejection signal being used by the detection mechanism 18 to determine whether the detect signal indicates potential precursor seismic activity or merely noise. If the rejection signal indicates merely noise, the frequency components produced by the filter function 74 are rejected by the detection mechanism 18; otherwise, the components are interpreted so as to determine whether precursor seismic activity is indicated by any one or more of the frequency components.

Turning to Figures 7A and 7B, the signal conditioning mechanism 16 comprises a first lead 76 and a second lead 78 connecting the mechanism 16 to the electromagnetic wave sensing mechanism 12. Where the sensing mechanism 12 comprises the AC power lines 13, the first lead 76 preferably is coupled to the hot or neutral lines of the wall socket 57 in a home, office or the like. Similarly, the second lead 78 preferably connects to the earth ground of such socket 57.

The comparison function 72 comprises a voltage divider 80 connected to the first lead 76 to receive the detect signal sensed by the electromagnetic wave sensing mechanism 12. The voltage divider 80 reduces the detect signal's voltage range to within the dynamic range of subsequent circuitry of the signal conditioning mechanism 16. As shown, resistor R1

preferably has a resistance of 180 Kilohm, and resistor R2 preferably has a resistance of 5 Kilohm. From the voltage divider 80, the detect signal is routed to a rectifier 82. The rectifier 82 preferably is a half-wave rectifier comprising a diode D1. As shown, the diode D1 is an 1N914, made by Motorola, Inc. of Schaumburg, Illinois. From the rectifier 82, the detect signal is routed to an analog-to-digital converter (ADC) 84 which produces the rejection signal by converting the detect signal from analog to digital. The rejection signal is provided to the detection mechanism 18 as described above.

The filter function 74 comprises a frequency-dependant voltage divider 86 so as to defeat undesirable frequency components of the detect signal. The voltage divider 86 preferably is implemented as a low-pass filter. As shown, the voltage divider 86 comprises two serially-connected resistors R3 connected to the sensing mechanism 12 by the first lead 76, and a grounded capacitor C1 that is connected at its grounded terminal to the second lead 78. Resistors R3 preferably each have resistances of 50 Kilohm, and capacitor C1 preferably has capacitance of 1 microfarad and is non-polarized. So implemented, the frequency-dependant voltage divider 86 defeats higher-frequency components and, in particular, reduces the 60 Hz/120 V line voltage to about every 5 V or less, peak to peak.

The detect signal is routed from the divider 86 to a low-pass filter 88 so as to further defeat undesirable high frequency components. The low-pass filter 88, as shown, is implemented using ganged active filters 90, as known to persons of ordinary skill in the art. The low-pass filter 88, so implemented, produces a relatively flat passband and a relatively steep stopband falloff. Although the low-pass filter 88 comprises two active filters 90, it is to be recognized that a greater or fewer number may be used without departing from the principles of the invention. Each active filter 90 comprises resistors R4 and capacitors C2 connected to an operational amplifier 92. Resistors R4 preferably have resistances of 50 Kilohm, and capacitors C2 preferably have

capacitances of 0.18 microfarad. The operation amplifier 92 preferably is a LM324 produced by National Semiconductor Corporation of Santa Clara, California. The active filters 90, so constructed, have cut-off frequencies of approximately 17.7 Hz.

The detect signal is routed from the low-pass filter 88 to an adjustable amplifier 96. The adjustable amplifier 96, as shown, is implemented using operational amplifier 98, resistor R6 and variable resistor R7, connected so as to form an inverting amplifier as is known in the art. The operational amplifier 98 preferably is the above-described LM324, made by National Semiconductor Corporation. The resistor R6 preferably has resistance of 10 Kilohm, and the variable resistor R7 preferably has maximum resistance of 100 Kilohm, so as to provide an amplifier having a maximum gain of 10. In operation, the gain of the adjustable amplifier 96 preferably is adjusted so as to amplify the detect signal and thereby increase the apparatus' sensitivity, while maintaining the detect signal's amplitude within the dynamic range of subsequent circuitry of the signal conditioning mechanism 16.

The low pass filter 88 preferably is coupled to the adjustable amplifier 96 using capacitor C3 and resistor R5. The capacitor 63 isolates the adjustable amplifier 96 from DC drift, if any, of the low pass filter 88. The resistor R5 overcomes any leakage of capacitor C3 so as to hold the inverting input terminal of the operation amplifier 98 at substantially 0V. Resistor R5 preferably has resistance of 1 megohm, and capacitor C3 preferably has a capacitance of 100 microfarad, and is non-polarized.

The detect signal is routed from the adjustable amplifier 96 through a coupling capacitor C4 to a predetermined plurality of frequency detect channels 100. The capacitor C4, as shown, preferably has a capacitance of 100 microfarad and is non-polarized so as to capacitively couple the adjustable amplifier 96 to the frequency detect channels 100.

In addition to the detect signal, each frequency detect channel 100 also receives a clock signal generated by a respective one of a plurality of clock generators 102. It is

to be recognized that the clock generators 102 may be implemented in any way known in the art without departing from the principles of the invention. Each frequency detect channel 100 produces an output signal that is routed to the analog to digital converter (ADC) 84.

Turning now to Figure 8, an exemplary frequency detect channel 100 is shown in greater detail. Each frequency detect channel 100 comprises a high-Q band-pass filter 104 and an AC-DC convertor 106. Each band-pass filter 104 preferably is implemented using one or more ganged MF10 universal monolithic switched capacitor filters, manufactured by National Semiconductor Corporation. As shown two such filters 108 and 110 are used. Each switched capacitor filter 108 and 110 has an input terminal 112, the input terminal 112 of filter 108 being capacitively coupled through capacitor C4 to the adjustable amplifier 96, so as to receive the detect signal. Each switched capacitor filter 108 and 110 also comprises a clock input terminal 114 connected to a respective one of the clock generators 102 so as to receive the clock signal generated thereby. Each of the switch capacitor filters 108 and 110 comprises an output terminal 116. The output terminal 116 of filter 108 is coupled to the input terminal 112 of filter 110, thereby ganging the filters 108 and 110 and providing for sufficient gain to maintain an adequate signal to noise ratio. The filters 108 and 110 are configured using a plurality of resistors R8 and a plurality of resistors R9. As shown in Figure 8, resistors R8 preferably have resistances of 91 Kilohm and resistors R9 preferably have resistance of 1 Megohm.

The band-pass filter 104 of each frequency detect channel 100 has a passband gain and Q determined by the resistances R8 and R9, and a frequency band determined by the frequency of the clock signal received at respective clock input terminal 114. That is, the center frequency of each of the band-pass filters 104 is directly dependant on the frequency of the clock signal generated by the respective clock generator 102. As shown in Figures 7A and 7B, the clock generators 102 generate clock signals from 100 Hz to 3,100 Hz in 200 Hz

increments. The band-pass filters 104 of respective frequency detect channels 100, in receipt of such clock signals, provide passbands having center frequencies of substantially 1 through 31 Hz, approximately in 2 Hz increments. The selection of resistances for resistors R8 and R9 determine the width of the pass bands. Using the resistances described above the pass band of each frequency detect channel 100 is approximately ± 0.5 Hz for the lower frequency bands (that is, 1-12 Hz) to ± 1.5 Hz for the higher frequency bands (that is, 12-31 Hz). Thence, the frequency detect channels 100, as shown, divide a predetermined bandwidth of the detect signal, i.e., 1 through 31 Hz, into 16 pass bands for routing to the ADC 84. It is to be recognized, however, that the detect signal's predetermined bandwidth may be less than or greater than 31 Hz, or may be divided into a greater or fewer number of passbands, or both, without departing from the principles of the invention.

In each frequency detect channel 100, the output terminal 116 of switched capacitor filter 110 is coupled to an associated AC-DC converter 106. Each AC-DC converter 106 comprises a rectifier 118 and a ripple filter 120. As shown, each rectifier 118 is an active circuit comprising an operational amplifier 122, resistors R10, R11 and R12, capacitor C5 and diodes D2 and D3, as known in the art. The operational amplifier 122 preferably is an LM324, made by National Semiconductor Corporation, the diodes D2 and D3 preferably are 1N914s, made by Motorola, Inc., the resistors R10 and R11 preferably have resistances of 20 Kiloohm, the resistor R12 preferably has resistance of 15 Kiloohm, and the capacitor C5 preferably has capacitance of 10 picofarad.

The rectifier 118 receives the detect signal from the associated switched capacitor filter 110 at the operational amplifier's inverting terminal. To that end, the rectifier 118 is coupled to the filter output terminal 116 through resistor R10. It is to be recognized that the detect signal, as received by each rectifier 118, comprises frequency components determined by the passband of the associated band-pass filter 104, that is, by the passband of the associated ganged switched capacitor filters 108 and 110.

Each ripple filter 120 preferably is a low-pass filter implemented so as to substantially remove ripple from the detect signal output by the AC-DC converter 106. As shown, the ripple filter 120 comprises an operational amplifier 124,
5 resistors R13, R14, R15 and R16, and capacitor C6, forming an active low-pass filter as is known in the art. The operational amplifier 124 preferably is an LM324, made by National Semiconductor Corporation, the capacitor C6 preferably has capacitance of 10 microfarad and the resistors
10 R13, R14, R15 and R16 preferably have resistances, respectively, of 20, 10, 22 and 6.2 Kilohm.

The filter 120 receives the detect signal at the operational amplifier's inverting terminal. The detect signal is received both from the switched capacitor filter 100, as
15 coupled through resistor R13 and from the rectifier 118, as coupled through resistor R14. The ripple filter 120 outputs the detect signal at output terminal 126, the output terminal 126 coupling the filter 120 to the ADC 84. It is to be recognized that the detect signal output to the ADC 84
20 comprises substantially DC levels representative of the peak amplitude of the frequency components passed by the associated ganged switched capacitor filters 108 and 110. The DC levels preferably are within the dynamic range of the ADC 84. That range typically is 0 to 5 volts.

The ADC 84, preferably is a multi-channel converter board. One such converter board is the Model AI016-P, made by Industrial Computer Source of San Diego, California. The ADC
25 84 converts to digital the outputs of each frequency detect channel 100, and provides the digital information to the detection mechanism 18. It is to be recognized, however, that the ADC 84 may comprise other structures, including a single converter together with a multiplexing mechanism, as are known
30 in the art, without departing from the principles of the invention.

The detection mechanism 18 receives from the ADC 84
35 digital signals representative of the detect signal as output by the filter function 74, in particular, as divided into a plurality of frequency-defined signals. The detection

mechanism 18 also receives from the ADC 84 the rejection signal produced by the comparison function 72, as described above. The detection mechanism 18 preferably receives all of these signals substantially simultaneously. However, it is to be recognized that the detection mechanism 18 may receive such signals individually or in various combination, without departing from the principles of the invention. For example, the detection mechanism 18 may receive, in turn, one filter function signal together with the comparison function's rejection signal.

The detection mechanism 18 preferably polls the ADC 84 at a predetermined rate, typically 1,000 times per second, for a predetermined time, typically 20 seconds. The detection mechanism 18 also polls in order to track the maximum peak amplitude of each channel over that predetermined time. The detection mechanism 18 preferably logs the maximum peak amplitude of each of the polled channels of the ADC, thereby conserving memory space which generally is subject to practical limitations. After the amplitudes are logged, the detection mechanism 18 resets, and repeats this polling and logging procedure.

In operation, as previously described, the detection mechanism 18 determines from the rejection signal whether the filter function's signals indicate potential precursor seismic activity, or merely noise. Noise is indicated when the peak amplitude of the rejection signal equals or exceeds a predetermined value. Noise is indicated, for example, if the rejection signal exhibits peak amplitude fluctuations of $\pm 3V$ at a frequency of about 60 Hz. If noise is indicated, the detection mechanism 18 rejects the filter function's signals for a predetermined time. In the case of 60 Hz noise, the detection mechanism 18 rejects the signals for 20 seconds (this 20 second period corresponding to the polling duration described previously), and continues to reject the signals in each subsequent 20 second period until noise is not indicated. If noise is not indicated, the detection mechanism 18 interprets the filter function's signals to confirm whether precursor seismic activity is indicated and, if so, to

forecast the occurrence and nature of the associated earthquake.

Precursor seismic activity is indicated when the peak amplitudes of a plurality of the respective signals produced by the filter function 74 equal or exceed a predetermined value over a predetermined time period. The exact plurality preferably is selected based on empirical calibration of the detect mechanism 18 so as to optimize the apparatus' performance. Typically, a majority of 10 to 12 channels comprise the selected plurality indicative of precursor seismic activity. The predetermined value generally is substantially the same for each channel, except at higher frequencies where the value may be decreased to compensate for losses associated with prior circuitry, particularly the filters of the signal conditioning mechanism 16. The predetermined value preferably is selected based on empirical calibration of the detection mechanism 18 so as to optimize the apparatus' performance. The predetermined time period also preferably is determined by empirical calibration. Typically, the time period is on the order of days. Empirical calibration is preferred because these parameters tend to vary with location, particularly because the depth of precursor seismic activity and other geophysical characteristics tend to vary geographically.

Turning to Figure 9, the detection mechanism's operation using the rejection signal and the filter function's signals is depicted. In step 140, the detection mechanism 18 determines whether noise is present based on the rejection signal's content. If noise is present, the filter function's signals are rejected in step 142. Otherwise, the filter function's signals are analyzed, in step 144, to determine whether the signal is substantially present for at least the predetermined time period. The signal need not be always present during that time period. If the filter function's signals are substantially present for that duration, the detection mechanism 18 produces, in step 146, one or more control signals to drive one or more alarms of the I/O stage 20, so as to indicate a potential impending earthquake.

If the filter function's signals are not present for that duration, the detection mechanism 18, in step 148, determines whether the filter function's signals have been inactive, i.e., lacking indications of precursor seismic activity, over a predetermined duration. Typically, the time period is on the order of hours, and preferably is determined by empirical calibration. If the signals have not been inactive, the detection mechanism 18 returns to step 144. Otherwise, the detection mechanism 18, in step 150, determines whether one or more alarms of the I/O stage 20 are currently on, that is, alerting of a potentially impending earthquake. If not, the detection mechanism 18 returns to step 144. If any alarm is currently on, the detection mechanism 18 produces, in step 152, one or more control signals to deactivate all alarms.

It will be appreciated that the method and apparatus for detecting precursor seismic activity according to the present invention provides certain significant advantages. In particular, an impending earthquake may be forecast by sensing one or more physical parameters so as to detect precursor seismic activity that may be indicated therein. In addition, an impending earthquake may be forecast at selected times in advance of the quake, each advance time associated with detections of precursor seismic activity in a respective one of the sensed physical parameters. Moreover, the apparatus is easy to use, economical, reliable and portable, allowing people to receive forecasts in their local area. By using the existing AC power grid the present invention makes detection of precursor seismic activity possible in areas of both high and low population density, as virtually anyone connected to the AC power grid may use the grid as an antenna to sense electromagnetic waves associated with precursor seismic activity. These and other important advantages of the invention will be apparent to those skilled in the art to which it pertains.

The foregoing description and disclosure of the method and apparatus has been directed to particular embodiments in accordance with the invention. It is evident, however, that many alternatives, modifications, and variations may be made

in the apparatus or method, or both, without departing from the principles of the invention.

5 The terms and expressions which have been employed in the foregoing specification are used therein as terms of description and not of limitation, and there is no intention in the use of such terms and expressions of excluding equivalents of the features shown and described or portions thereof, it being recognized that the scope of the invention is defined and limited only by the claims which follow.

What is claimed is:

1. A method for detecting precursor seismic activity, comprising:

5 employing AC power lines to sense electromagnetic waves associated with precursor seismic activity and produce electrical signals representative of said sensed electromagnetic waves; and

10 examining said electrical signals to detect said electromagnetic waves associated with precursor seismic activity.

2. An apparatus for detecting precursor seismic activity, comprising:

15 an acoustic wave sensing mechanism for producing an electrical signal representative of sensed acoustic waves; and

20 a detection circuit, responsive to said electrical signal, having a slope up detector, a slope down detector and a slope comparator, said slope comparator producing an indication of the presence of precursor seismic activity when the signal produced by said slope up detector exceeds the signal produced by said slope down detector.

- 25 3. An apparatus for detecting precursor seismic activity, comprising:

 an electromagnetic wave sensing mechanism for producing an electrical signal representative of sensed electromagnetic waves;

30 a detection circuit, responsive to said electrical signal, having a presence detector so as to produce

a presence signal indicative of precursor seismic activity when the amplitude of said detect signal is at least equal to the amplitude of a predetermined threshold signal.

- 5 4. An apparatus for detecting precursor seismic activity, comprising:

an electromagnetic wave sensing mechanism for producing an electrical signal representative of sensed electromagnetic waves;

10 a first signal conditioning circuit having a filter function and a comparison function, said filter function receiving said electrical signal and producing detect signals of predetermined bandwidths, and said comparison function receiving
15 said electrical signal and producing a rejection signal; and

a detection circuit, responsive said rejection signal and said detect signals, so as to reject said detect signals if the detect signals indicate noise.

20

5. A method for detecting precursor seismic activity, comprising the steps of:

sensing acoustic waves of selected frequencies;

25

producing an electrical signal representative of said sensed acoustic waves;

detecting the respective slopes of upwardly and downwardly directed transitions of said electrical signal;

comparing said respective slopes; and

producing a comparator signal to indicate the presence of precursor seismic activity when said slope of said upwardly directed transition exceeds said slope of said downwardly directed transition.

- 5 6. A method for detecting precursor seismic activity, comprising the steps of:

sensing electromagnetic waves having selected frequencies;

10 producing an electrical signal representative of said sensed electromagnetic waves;

comparing said electrical signal to a predetermined threshold signal; and

15 producing a presence signal indicative of precursor seismic activity when the amplitude of said detect signal is at least equal to the amplitude of said threshold signal.

7. A method for detecting precursor seismic activity, comprising the steps of:

20 sensing electromagnetic waves having predetermined frequencies;

producing an electrical signal representative of said sensed electromagnetic waves;

filtering said electrical signal to produce detect signals having selected bandwidths;

25 producing a rejection signal from said electrical signal;

determining from said rejection signal whether said detect signals indicate noise; and

rejecting said detect signals when said detect signals are determined to indicate noise.

8. An apparatus for sensing infrasonic acoustic waves and producing an electrical signal representative of sensed infrasonic acoustic waves, comprising:

a body having a chamber, said chamber having an outer portion, a middle portion and an inner portion, said inner portion having a wall;

a diaphragm having a base and a substantially domed shape and enclosing a predetermined volume, said diaphragm affixed to said body adjacent said outer portion of said chamber so as to form a sealed cavity, said cavity including said predetermined volume of said diaphragm and said chamber;

a magnet disposed in said inner portion, affixed to said wall and producing a magnetic field;

a first transmission element disposed in said outer portion and affixed to said diaphragm, said diaphragm being sensitive to acoustic waves having infrasonic frequencies;

a coil disposed in said inner portion, adjacent said magnet, and having a predetermined shape adapted to accommodate motion of said coil within said inner portion relative to said magnet; and

a connector disposed through said middle portion of said chamber, said connector affixed at one end to said first transmission element and at the other end to said coil so that, when infrasonic acoustic waves deflect said diaphragm, said deflection is transmitted to said coil, causing said coil to move through said magnetic field of said magnet so as to

induce an electrical signal in said coil
representative of the infrasonic acoustic waves,
said diaphragm, transmission element and coil having
a frequency response selected so as to be maximal
over a range of frequencies associated with
precursor seismic activity.

9. An apparatus for detecting precursor seismic activity,
comprising:

an acoustic transducer having a body, said body having a
chamber, said chamber having an outer portion, a
middle portion and an inner portion, said inner
portion having a wall;

a diaphragm having a base and a substantially domed
shape and enclosing a predetermined volume,
said diaphragm affixed to said body adjacent
said outer portion of said chamber so as to
form a sealed cavity, said cavity including
said predetermined volume of said diaphragm and
said chamber;

a magnet disposed in said inner portion, affixed to
said wall and producing a magnetic field;

a first transmission element disposed in said outer
portion and affixed to said diaphragm, said
diaphragm being sensitive to acoustic waves
having infrasonic frequencies;

a coil disposed in said inner portion, adjacent said
magnet, and having a predetermined shape
adapted to accommodate motion of said coil
within said inner portion relative to said
magnet; and

a connector disposed through said middle portion of
said chamber, said connector affixed at one end
to said first transmission element and at the
other end to said coil so that, when infrasonic
acoustic waves deflect said diaphragm, said
deflection is transmitted to said coil, causing
said coil to move through said magnetic field
of said magnet so as to induce an electrical
signal in said coil representative of the
infrasonic acoustic waves, said diaphragm,
transmission element and coil having a
frequency response selected so as to be maximal
over a range of frequencies associated with
precursor seismic activity.

5

10




$\frac{1}{8}$ 

Fig.1

2\8

**Fig. 2****Fig. 3**

3/8




Fig. 4

4/8




Fig.5




Fig. 7A

6/8




Fig.7B






Fig.8



INTERNATIONAL SEARCH REPORT

International application No.

PCT/US94/02626

A. CLASSIFICATION OF SUBJECT MATTER

IPC(5) : Please See Extra Sheet.

US CL : Please See Extra Sheet.

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 324/72,323,344; 73/654;181/122;340/310R,601,690;343/720;367/135;455/270

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

324/72,323,344,345,508,509;181/101,122;73/652,654,517R,517AV; 340/310R,310A,601,689,690;343/720;367/135,182-184,188; 455/270

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

APS

C. DOCUMENTS CONSIDERED TO BE RELEVANT

| Category* | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
|-----------|--|-----------------------|
| A | US, A, 2,553,734 (ADLER) 22 MAY 1951 | 1 |
| A | US, A, 3,866,111 (WARREN) 11 FEBRUARY 1975 | 1 |
| A | US, A, 5,151,838 (DOCKERY) 29 SEPTEMBER 1992 | 1 |
| A | US, A, 4,704,693 (THOMAS) 03 NOVEMBER 1987 | 2,5 |
| A | US, A, 4,064,480 (HOWLETT) 20 DECEMBER 1977 | 2,5 |
| Y | US, A, 4,132,947 (WEISCHEDEL ET AL) 02 JANUARY 1979 (see col. 2, lines 8-37) | 2,5 |
| Y | US, A, 4,724,390 (RAUSCHER ET AL) 09 FEBRUARY 1988 (see col. 4, lines 13-29) | 3,4,6,7 |

☒ Further documents are listed in the continuation of Box C.
 ☐ See patent family annex.

| | | |
|---|-----|--|
| * Special categories of cited documents: | *T | later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention |
| *A* document defining the general state of the art which is not considered to be part of particular relevance | *X* | document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone |
| *E* earlier document published on or after the international filing date | *Y* | document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art |
| *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) | *G* | document member of the same patent family |
| *O* document referring to an oral disclosure, use, exhibition or other means | | |
| *P* document published prior to the international filing date but later than the priority date claimed | | |

Date of the actual completion of the international search

06 OCTOBER 1994

Date of mailing of the international search report

OCT 20 1994

 Name and mailing address of the ISA/US
 Commissioner of Patents and Trademarks
 Box PCT
 Washington, D.C. 20231

Facsimile No (703) 305-3230

Authorized officer:

GERARD R. STRECKER

Telephone No. (703) 305-4937

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US94/02626

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

| Category* | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
|-----------|--|-----------------------|
| Y | US, A, 5,148,110 (HELMS) 15 SEPTEMBER 1992 (see col. 3, lines 52-60 | 3,4,6,7 |
| A | US, A, 4,884,030 (NAVILLE ET AL) 28 NOVEMBER 1989 | 3,4,6,7 |
| A | US, A, 3,067,404 (HILDEBRANDT) 04 DECEMBER 1962 | 8,9 |
| A | US, A, 3,953,829 (BOYLE) 27 APRIL 1976 | 8,9 |
| A | US, A, 4,657,025 (ORLANDO) 14 APRIL 1987 | 8,9 |
| A | US, A, 4,612,506 (VAROTSOS ET AL) 16 SEPTEMBER 1986 | 3,6 |

BEST AVAILABLE COPY

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US94/02626**Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)**

This international report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)This International Searching Authority found multiple inventions in this international application, as follows:
Telephone Practice
Please See Extra Sheet.

1. ☒ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
☐ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US94/02626

A. CLASSIFICATION OF SUBJECT MATTER:

IPC (5):

G01V 1/16, 1/28, 3/12; G01H 1/00, 11/10; H04B 13/02; H01Q 1/46; H04R 9/00

A. CLASSIFICATION OF SUBJECT MATTER:

US CL :

324/72,323,344; 73/654;181/122;340/310R,601,690;343/720;367/135;455/270

BOX II. OBSERVATIONS WHERE UNITY OF INVENTION WAS LACKING

This ISA found multiple inventions as follows:

Claims 1, 3, 4, 6, 7 of Group I are drawn to an electromagnetic wave method and apparatus for detecting precursor seismic activity, classified in class 324, subclass 344.

Claims 2 and 5 of Group II are drawn to an acoustic wave method and apparatus including slope detection circuitry for detecting precursor seismic activity, classified in class 367 subclass.

Claims 8 and 9 of Group III are drawn to an apparatus for sensing acoustic waves or precursor seismic activity having specific acoustic transducer structure, classified in class 367 subclass 182.

The above inventions lack unity under PCT Rule 13 since they involve different inventive concepts embodying different structural features. Thus the method and apparatus of Group I does not require the acoustic sensing of Groups II and III and the acoustic sensing method and apparatus of Groups II and III do not require the electromagnetic wave sensing of Group I. Nor does the method and apparatus of Group II require the acoustic transducer of Group III. The inventions of the three groups do not share a common special technical feature.

BEST AVAILABLE COPY